

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

Title: METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE**IN THE CLAIMS**

Please amend claims 1, 16, and 35 as follows:

1. (Currently Amended) A method performed in an interconnect device to allocate resource capacity, ~~within the interconnect device in accordance with a resource allocation table, the resource allocation table including a plurality of allocation entries indicating an allocation of the resource capacity to a plurality of resource consumers comprising a plurality of data streams supported by the interconnect device, wherein the resource capacity comprises bandwidth on a physical link shared by the plurality of data streams supported by the interconnect device,~~ the method including:

generating a resource allocation table including a plurality of allocation entries indicating an allocation of the resource capacity to a plurality of resource consumers comprising a plurality of data streams supported by the interconnect device, wherein the resource capacity comprises bandwidth on a physical link shared by the plurality of data streams supported by the interconnect device;

retrieving a ranking vector corresponding to a first allocation entry within the allocation table;

generating a pending request vector indicating for which of the plurality of resource consumers a resource request is pending; and

selecting a selected resource consumer to consume at least a portion of the resource capacity, the selection being performed utilizing the ranking vector and the pending request vector,

wherein the ranking vector is derived from the resource allocation table and comprises a list of resource consumers of the plurality of resource consumers, the list being ordered in accordance with an order of appearance of a first allocation entry for a respective resource consumer within the resource allocation table.

2. (Original) The method of claim 1 wherein the order of appearance is determined in a first direction within the resource allocation table from the first allocation entry.

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

Title: METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE

3. (Original) The method of claim 1 wherein the selection of the selected resource consumer is performed combinatorially utilizing the ranking vector and the pending request vector.
4. (Cancelled).
5. (Original) The method of claim 1 wherein the ranking vector is retrieved from a ranking table, the ranking table comprising a plurality of ranking vectors, each of which corresponds to an entry within the resource allocation table.
6. (Original) The method of claim 5 wherein the retrieval of the ranking vector includes utilizing a resource allocation table index pointer, identifying the first allocation entry within the resource allocation table, to retrieve the ranking vector from the ranking table.
7. (Original) The method of claim 1 wherein a second allocation entry within the resource allocation table records the allocation of none of the resource capacity to a second resource consumer, and wherein the second allocation entry is excluded from consideration as a first entry for the second resource consumer within the resource allocation table.
8. (Original) The method of claim 1 wherein the resource allocation table includes multiple allocation entries for a first resource consumer of the plurality of resource consumers.
9. (Original) The method of claim 1 wherein the selection of the selected resource consumer is performed utilizing combinational logic that selects a highest order resource consumer, within the ranking vector and for which a request is pending, as the selected resource consumer.
10. (Original) The method of claim 9 wherein the selection of the selected resource consumer performed utilizing the combinational logic is performed in one clock cycle.

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

Title: METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE

11. (Original) The method of claim 1 wherein the generation of the pending request vector includes examining a respective request queue associated with each of the plurality of resource consumers to determine whether the respective request queue includes a resource request associated with the respective resource consumer.

12. (Previously Presented) The method of claim 1 including, subsequent to the selection of the selected resource consumer, updating a resource allocation table index pointer to point to a second allocation entry within the resource allocation table.

13. (Original) The method of claim 12 wherein the second allocation entry corresponds to the selected resource consumer if the resource capacity allocated to the selected resource consumer is not consumed by at least one resource request associated with the selected resource consumer.

14. (Original) The method of claim 13 wherein the second allocation entry corresponds to a further resource consumer, downstream of the selected resource consumer within the resource allocation table, if the resource capacity allocated to the selected resource consumer is consumed by at least one resource request associated with the selected resource consumer.

15. (Original) The method of claim 12 wherein the updating of the resource allocation table index pointer includes retrieving a first resource allocation table bit vector associated with the selected resource consumer, the first resource allocation table bit vector including a bit entry corresponding to each allocation entry within the resource allocation table, at least one of the bit entries being set to flag at least one allocation entry for the selected resource consumer within the resource allocation table.

16. (Currently Amended) A system in an interconnect device, the system configured to allocate resource capacity within the interconnect device, in accordance with a resource allocation table, the resource allocation table including a plurality of allocation entries indicating an allocation of the resource capacity to a plurality of the resource consumers comprising a plurality of data streams supported by the interconnect

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

Title: METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE

~~device, wherein the resource capacity comprises bandwidth on a physical link shared by the plurality of data streams supported by the interconnect device, the system including:~~

a memory to store ~~the a~~ resource allocation table and a ranking table, and to output a ranking vector, from the ranking table, corresponding to a first allocation entry within the allocation table; the resource allocation table including a plurality of allocation entries indicating an allocation of the resource capacity to a plurality of the resource consumers comprising a plurality of data streams supported by the interconnect device, wherein the resource capacity comprises bandwidth on a physical link shared by the plurality of data streams supported by the interconnect device;

a resource allocator to generate a pending request vector indicating for which of the plurality of resource consumers a resource request is pending; and

a selector to select a selected resource consumer to consume at least a portion of the resource capacity, the selection being performed by the selector utilizing the ranking vector and the pending request vector,

wherein the ranking vector is derived from the resource allocation table and comprises a list of resource consumers of the plurality of resource consumers, the list being ordered in accordance with an order of appearance of a first allocation entry for a respective resource consumer within the resource allocation table.

17. (Original) The system of claim 16 wherein the order of appearance is determined in a first direction within the resource allocation table from the first allocation entry.

18. (Original) The system of claim 16 wherein the selector comprises combinational logic to combinatorially utilize the ranking vector and the pending request vector to select the selected resource consumer.

19. (Cancelled).

20. (Original) The system of claim 16 wherein the ranking table comprising a plurality of ranking vectors, each of which corresponds to an entry within the resource allocation table.

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

**Title: METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE**

21. (Original) The system of claim 20 wherein the memory maintains a resource allocation table index pointer, and wherein the ranking vector is outputted from the memory utilizing the resource allocation table index pointer, the resource allocation table index pointer identifying the first allocation entry within the resource allocation table.
22. (Original) The system of claim 16 wherein a second allocation entry within the resource allocation table records the allocation of none of the resource capacity to a second resource consumer, and wherein the second allocation entry is excluded from consideration as a first entry for the second resource consumer within the resource allocation table.
23. (Original) The system of claim 16 wherein the resource allocation table includes multiple allocation entries for a first resource consumer of the plurality of resource consumers.
24. (Original) The system of claim 16 wherein the selector comprises combinational logic to select a highest order resource consumer, within the ranking vector and for which a request is pending, as the selected resource consumer.
25. (Original) The system of claim 24 wherein the selector operates to select the selected resource consumer within one clock cycle.
26. (Original) The system of claim 16 wherein the resource allocator is to examine a respective request queue associated with each of the plurality of resource consumers to determine whether the respective request queue includes a resource request associated with the respective resource consumer.
27. (Previously Presented) The system of claim 16 including a further selector, subsequent to the selection of the selected resource consumer, to update a resource allocation table index pointer to point to a second allocation entry within the resource allocation table.

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

**Title: METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE**

28. (Previously Presented) The system of claim 27 wherein the second allocation entry corresponds to the selected resource consumer if the resource capacity allocated to the selected resource consumer is not consumed by at least one resource request associated with the selected resource consumer.
29. (Original) The system of claim 28 wherein the second allocation entry corresponds to a further resource consumer, downstream of the selected resource consumer within the resource allocation table, if the resource capacity allocated to the selected resource consumer is consumed by at least one resource request associated whether the selected resource consumer.
30. (Original) The system of claim 27 wherein the updating of the resource allocation table index pointer by the further selector includes retrieving a first resource allocation table bit vector associated with the selected resource consumer, the first resource allocation table bit vector including a bit entry corresponding to each allocation entry within the resource allocation table, at least one of the bit entries being set to flag at least one allocation entry for the selected resource consumer within the resource allocation table.
31. (Previously Presented) A machine-readable medium storing a description of a circuit, said circuit comprising:
- a memory to store a resource allocation table and a ranking table, and to output a ranking vector, from the ranking table, corresponding to a first allocation entry within the allocation table, the resource allocation table including a plurality of allocation entries indicating an allocation of a resource capacity to a plurality of resource consumers comprising a plurality of data streams, wherein the resource capacity comprises bandwidth on a physical link shared by the plurality of data streams;
 - a resource allocator to generate a pending request vector indicating for which of the plurality of resource consumers a resource request is pending; and
 - a selector to select a selected resource consumer to consume at least a portion of the resource capacity, the selection being performed by the selector utilizing the ranking vector and the pending request vector,

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

Title: METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE

wherein the ranking vector is derived from the resource allocation table and comprises a list of resource consumers of the plurality of resource consumers, the list being ordered in accordance with an order of appearance of a first allocation entry for a respective resource consumer within the resource allocation table.

32. (Original) The machine-readable medium of claim 31 wherein the description comprises a behavioral level description of the circuit.

33. (Previously Presented) The machine-readable medium of claim 32 wherein the behavioral level description is compatible with a Very high speed integrated circuit Hardware Description Language (VHDL) format.

34. (Original) The machine-readable medium of claim 32 wherein the behavioral level description is compatible with a Verilog format.

35. (Currently Amended) A system in an interconnect device, the system configured to allocate resource capacity within an interconnect device, ~~in accordance with a resource allocation table, the resource allocation table including a plurality of allocation entries indicating an allocation of the resource capacity to a plurality of resource consumers comprising a plurality of data streams supported by the interconnect device, wherein the resource capacity comprises bandwidth on a physical link shared by the plurality of data streams supported by the interconnect device,~~ the system including:

first means for storing ~~the a~~ resource allocation table and a ranking table, and for outputting a ranking vector, from the ranking table, corresponding to a first allocation entry within the allocation table; the resource allocation table including a plurality of allocation entries indicating an allocation of the resource capacity to a plurality of resource consumers comprising a plurality of data streams supported by the interconnect device, wherein the resource capacity comprises bandwidth on a physical link shared by the plurality of data streams supported by the interconnect device;

second means for generating a pending request vector indicating for which of the plurality of resource consumers a resource request is pending; and

Amendment and Response

Applicant: Varaprasad Vajjhala et al.

Serial No.: 09/977,511

Filed: October 12, 2001

Docket No.: 10011257-1

Title: **METHOD AND SYSTEM TO ALLOCATE RESOURCES WITHIN AN INTERCONNECT DEVICE
ACCORDING TO A RESOURCE ALLOCATION TABLE**

third means for selecting a selected resource consumer to consume at least a portion of the resource capacity, the selection being performed by third means utilizing the ranking vector and the pending request vector,
wherein the ranking vector is derived from the resource allocation table and comprises a list of resource consumers of the plurality of resource consumers, the list being ordered in accordance with an order of appearance of a first allocation entry for a respective resource consumer within the resource allocation table.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☒ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.